

# LC2150-AN

## 1.3MP HD Network IR Bullet Camera



### Features

#### Excellent Image Quality

- 1.3 Megapixel 1/3" progressive scan CMOS sensor
- High definition and smooth picture, 960p@30fps
- H.264 high profile video codec, saves up to 30% bandwidth and storage
- Low illumination, 0.01lux with color picture
- WDR support / 3D noise reduction

#### Integrated High Efficiency IR

- Industrial IR LED with long operational lifespan
- 30 ~ 50m IR distance
- Smart IR function

#### A Variety of Installation Modes

- Supports 90°, 180°, 270° image rotation

#### Abundant Functions and Features

- TF card slot, supports Automatic Network Replenishment (ANR)
- Up to 3 video streams
- PoE
- IP66

### Specifications

	LC2150-AN(-IR2, -IR3, -IR4, -IR5, -IR6)
<b>Camera</b>	
Image Sensor	1/3" progressive scan CMOS
Pixels	1.3 Megapixel
Min. Illumination	Color: 0.01lux @ (F1.6, AGC ON)
Shutter Speed	B/W: 0lux with IR
Day / Night	1/10 ~ 1/10,000s
Wide Dynamic Range	Auto (ICR) / Color / B/W
S/N Ratio	Digital WDR
White Balance	>50dB
Gain Control	Auto / Manual
Backlight Compensation	Off / BLC / WDR
<b>Lens</b>	
Mount Type	M12
Focal Length	3.6mm (-IR2) / 6mm (-IR3) / 8mm (-IR4) / 12mm (-IR5) / 16mm (-IR6)
Angle of View	75.6° (-IR2) / 46.7° (-IR3) / 35.3° (-IR4) / 23° (-IR5) / 16.9° (-IR6)
<b>Infrared</b>	
IR LED	1 pc IR LED(-IR2, -IR3, -IR4) 2 pcs IR LED(-IR5, -IR6)
IR Distance	30m (-IR2, -IR3, -IR4) 50m (-IR5, -IR6)
IR Intensity	Smart IR
<b>Video</b>	
Compression	H.264 / MJPEG
Image Resolution	Main stream: 960p Secondary stream: D1
Frame Rate	Main stream: 960p@30fps Secondary stream: D1@30fps
Bitrate	32kbps ~ 16Mbps
Bitrate Control	VBR / CBR
Multi-stream	Supported
Caption	Date and time / Alarm / Customized
Privacy Masking	Up to 4 zones
Motion Detection	Up to 4 zones
Video Freeze	Supported
Digital Noise Reduction	3D noise reduction
Image Flip	Flip / Mirror / Rotation at 90°, 180°, 270°
<b>Network</b>	
Network Protocols	TCP/IP, UDP, HTTP, DHCP, DNS/DDNS, RTP/RTCP, RTSP, PPPoE, FTP, VSIP, UPnP, 802.1x, IPv4, IPv6 (optional)
User Interface	IPC Control (IE, Firefox, Chrome)
Max. User Access	Max. 10 Users (includes 2 internal)
Application Programming	ONVIF (Profile S), GB/T 28181-2011, API, CGI
Automatic Network Replenishment (ANR)	Supported
<b>Alarm</b>	
Alarm Triggers	Motion detection / Shield area / Network disconnect / Disk full / Disk Error
Alarm Events	Alarm report / Recording / Alarm caption / Snapshot
<b>Interfaces</b>	
Ethernet	10/100M, RJ45 interface
Memory Slot	TF card slot, supports up to 128GB
<b>Environmental</b>	
Operating Temperature	-30°C ~ 60°C / -22°F ~ 140°F
Operating Humidity	10% ~ 95%
Protection Level	IP66
<b>Electrical</b>	
Power	12V DC ± 10% / PoE (IEEE802.3af)
Power Consumption	Max. 10W
<b>Mechanical</b>	
Weight	1kg / 2.2lb (Gross Weight)
Dimensions	181.5 x 80 x 73mm / 7.15" x 3.15" x 2.87"

### Dimensions

Units:mm

